

Ecoline

The easy entry into automated pastry production.



The Ecoline is a compact make-up line which allows you to begin automated production for folded and rolled pastry products. Designed and manufactured in our factory in Switzerland, it unites all the qualities that characterise RONDO machines at a low price.

The benefits at a glance

Compact design

- Two different lengths
- Length with dough band positioner: 4.2 m / 6.2 m
- Length with calibrator: 5.4 m / 7.4 m

High process reliability

- Twin cutting station with counter-pressure rollers
- Precise belt drive at product discharge
- Consistent cutting length through intelligent drive concept

Simple operation

- Touch panel interface for controlling the line, the guillotine and two driven accessories
- 99 storable programs

High flexibility

- A wide variety of accessories for many different types of products
- Unique decorating cutting rollers for customising products
- Moveable Guillotine for high flexibility

High reliability

- Swiss-made
- Worldwide RONDO Service
- Meets international safety standards

Standard equipment

- Twin cutting station with counter-pressure rollers
- Movable guillotine with knife and hold-down device
- Quick-release belt
- Touch panel
- Dough band positioner
- Holder for cutting rollers
- Bottom plate

Starter Kit Accessory

- Length cutting shaft with six knives
- Gauge for setting the cutting blades
- Holder for folding shoes
- Folding shoes for 4-row production of
 - Single-fold products
 - Double-fold products with seal on top
 - Double-fold products with seal on bottom

Options

- Ecoline Calibrator
- Accessories

Filling depositors

- Mechanical filling depositor for 4- or 6-row production
- Fix installed pneumatic filling depositor for 4- or 6-row production
- Moveable pneumatic filling depositor for 4- or 6-row production

Technical data

Ecoline	SEL401	SEL601
Total length	4.0 m	6.0 m
Length with dough band positioner	4.2 m	6.2 m
Length with Ecoline Calibrator	5.4 m	7.4 m
Table width	715 mm	
Table height	915 mm	
Working width	600 mm	
Belt speed	0.5 – 8 m/min	
Running direction	right - left	
Drive	on outfeed side	
Supply voltage	3 × 200 – 480 V, 50/60 Hz	
Control voltage	24 V DC	
Operation	<ul style="list-style-type: none"> • Microprocessor control system • Touch panel • 99 program memory slots 	
Max. number of driven accessories	2	
Interfaces	to the calibrator	

The right to make changes of a technical nature is reserved. The technical safety and type-specific instructions in the operating manual must be complied with. Prohibition, information and warning signs on the machines are to be complied with in accordance with the operating instructions.



RONDO

Dough-how & more.

RONDO Burgdorf AG

Heimiswilstrasse 42
3400 Burgdorf/Switzerland
Tel. +41 (0)34 420 81 11
Fax +41 (0)34 420 81 99
info@rondo-online.com

RONDO Schio s.r.l.

Via Lago di Albano, 86
36015 Schio (VI)/Italy
Tel. +39 0445 575 429
Fax +39 0445 575 317
info.it@rondo-online.com

RONDO GmbH & Co. KG

Hoorwaldstrasse 44
57299 Burbach/Germany
Tel. +49 (0)2736 203-0
Fax +49 (0)2736 203130
info.de@rondo-online.com

RONDO S.à.r.l.

PAE «Les Pins»
67319 Wasselonne Cedex/France
Tel. +33 (0)3 88 59 11 88
Fax +33 (0)3 88 59 11 77
info.fr@rondo-online.com

RONDO Ltd.

Unit 7, Chessington Park
Lion Park Avenue
Chessington, Surrey KT9 1ST/UK
Tel. +44 (0)20 8391 1377
Fax +44 (0)20 8391 5878
info.uk@rondo-online.com

000 RONDO Rus

Dmitrovskoye chaussee, 163A, b. 2
Office 18.5 / Business Center SK Plaza
127495 Moscow/Russia
Tel. +7 (495) 419 51 23
Fax +7 (495) 419 51 25
info.ru@rondo-online.com

RONDO Asia

Regional Office
A-2-21, Jalan Kuchai Maju 2
Kuchai Entrepreneurs Park
Jalan Kuchai Lama
58200 Kuala Lumpur/Malaysia
Tel. +60 3 7984 55 20
Fax +60 3 7984 55 95
info.my@rondo-online.com

RONDO Inc.

100 State Street
Moonachie, N.J. 07074/USA
Tel. +1 201 229 97 00
Fax +1 201 229 00 18
info.us@rondo-online.com

RONDO Inc.

267 Canarctic Drive
Downsview, Ont. M3J 2N7/Canada
Tel. +1 416 650 0220
Fax +1 416 650 9540
info.ca@rondo-online.com

www.rondo-online.com